CONTENDER
Performance Products

PC 2000
PERMA SEAL CO2 OUTLET SEAL

It is recommended to lubricate the O ring on both sides with a thin coat of oil or grease before installing the Perma Seal in your regulator. Install with a 5/32" allen wrench by screwing the Perma Seal into the threads of your bottle valve. Do not overtighten. Tighten to snug only. It is only necessary to be tight enough to hold the brass supported O ring in place. Overtightening will cause the seal to seperate.

? QUESTIONS ?

If you have any questions or concerns on the installation or use of this product, DO NOT contact the retailer you purchased this item from. Most retailers are not equipped to help with in-depth tech questions.

FOR HELP PLEASE CONTACT:

CONTENDER PERFORMANCE PRODUCTS INC.
PHONE: 740-281-0136
www.contenderperformance.com

CONTENDER
Performance Products

PC 2000
PERMA SEAL CO2 OUTLET SEAL

It is recommended to lubricate the O ring on both sides with a thin coat of oil or grease before installing the Perma Seal in your regulator. Install with a 5/32" allen wrench by screwing the Perma Seal into the threads of your bottle valve. Do not overtighten. Tighten to snug only. It is only necessary to be tight enough to hold the brass supported O ring in place. Overtightening will cause the seal to seperate.

? QUESTIONS ?

If you have any questions or concerns on the installation or use of this product, DO NOT contact the retailer you purchased this item from. Most retailers are not equipped to help with in-depth tech questions.

FOR HELP PLEASE CONTACT:

CONTENDER PERFORMANCE PRODUCTS INC.
PHONE: 740-281-0136
www.contenderperformance.com

CONTENDER
Performance Products

PC 2000
PERMA SEAL CO2 OUTLET SEAL

It is recommended to lubricate the O ring on both sides with a thin coat of oil or grease before installing the Perma Seal in your regulator. Install with a 5/32" allen wrench by screwing the Perma Seal into the threads of your bottle valve. Do not overtighten. Tighten to snug only. It is only necessary to be tight enough to hold the brass supported O ring in place. Overtightening will cause the seal to seperate.

? QUESTIONS ?

If you have any questions or concerns on the installation or use of this product, DO NOT contact the retailer you purchased this item from. Most retailers are not equipped to help with in-depth tech questions.

FOR HELP PLEASE CONTACT:

CONTENDER PERFORMANCE PRODUCTS INC.
PHONE: 740-281-0136
www.contenderperformance.com

CONTENDER
Performance Products

PC 2000
PERMA SEAL CO2 OUTLET SEAL

It is recommended to lubricate the O ring on both sides with a thin coat of oil or grease before installing the Perma Seal in your regulator. Install with a 5/32" allen wrench by screwing the Perma Seal into the threads of your bottle valve. Do not overtighten. Tighten to snug only. It is only necessary to be tight enough to hold the brass supported O ring in place. Overtightening will cause the seal to seperate.

? QUESTIONS ?

If you have any questions or concerns on the installation or use of this product, DO NOT contact the retailer you purchased this item from. Most retailers are not equipped to help with in-depth tech questions.

FOR HELP PLEASE CONTACT:

CONTENDER PERFORMANCE PRODUCTS INC.
PHONE: 740-281-0136
www.contenderperformance.com