CONTENDER
Performance Products

PC 410
12 Volt 4 Way Air/CO2 Solenoid Valve
MAXIMUM PRESSURE 125 PSI
All Ports are 1/8" NPT

*Port #1 is air / CO2 supply
*Port #3 is exhaust
*Port #2 is air / CO2 out
*Port #4 is air / CO2 out

Brass screws marked #2 and #4 are adjustable to control the flow rate of ports #2 and #4. Screwed in clockwise decreases rate and counterclockwise increases the rate.
Needles and seats are brass.
Please do not over-tighten these screws.

? QUESTIONS ?

If you have any questions or concerns on the installation or use of this product, DO NOT contact the retailer you purchased the kit from. Most retailers are not equipped to help with in-depth tech questions.

CONTENDER PERFORMANCE PRODUCTS INC.
PHONE: 740-281-0136
www.contenderperformance.com

CONTENDER
Performance Products

PC 410
12 Volt 4 Way Air/CO2 Solenoid Valve
MAXIMUM PRESSURE 125 PSI
All Ports are 1/8" NPT

*Port #1 is air / CO2 supply
*Port #3 is exhaust
*Port #2 is air / CO2 out
*Port #4 is air / CO2 out

Brass screws marked #2 and #4 are adjustable to control the flow rate of ports #2 and #4. Screwed in clockwise decreases rate and counterclockwise increases the rate.
Needles and seats are brass.
Please do not over-tighten these screws.

? QUESTIONS ?

If you have any questions or concerns on the installation or use of this product, DO NOT contact the retailer you purchased the kit from. Most retailers are not equipped to help with in-depth tech questions.

CONTENDER PERFORMANCE PRODUCTS INC.
PHONE: 740-281-0136
www.contenderperformance.com

CONTENDER
Performance Products

PC 410
12 Volt 4 Way Air/CO2 Solenoid Valve
MAXIMUM PRESSURE 125 PSI
All Ports are 1/8" NPT

*Port #1 is air / CO2 supply
*Port #3 is exhaust
*Port #2 is air / CO2 out
*Port #4 is air / CO2 out

Brass screws marked #2 and #4 are adjustable to control the flow rate of ports #2 and #4. Screwed in clockwise decreases rate and counterclockwise increases the rate.
Needles and seats are brass.
Please do not over-tighten these screws.

? QUESTIONS ?

If you have any questions or concerns on the installation or use of this product, DO NOT contact the retailer you purchased the kit from. Most retailers are not equipped to help with in-depth tech questions.

CONTENDER PERFORMANCE PRODUCTS INC.
PHONE: 740-281-0136
www.contenderperformance.com

CONTENDER
Performance Products

PC 410
12 Volt 4 Way Air/CO2 Solenoid Valve
MAXIMUM PRESSURE 125 PSI
All Ports are 1/8" NPT

*Port #1 is air / CO2 supply
*Port #3 is exhaust
*Port #2 is air / CO2 out
*Port #4 is air / CO2 out

Brass screws marked #2 and #4 are adjustable to control the flow rate of ports #2 and #4. Screwed in clockwise decreases rate and counterclockwise increases the rate.
Needles and seats are brass.
Please do not over-tighten these screws.

? QUESTIONS ?

If you have any questions or concerns on the installation or use of this product, DO NOT contact the retailer you purchased the kit from. Most retailers are not equipped to help with in-depth tech questions.

CONTENDER PERFORMANCE PRODUCTS INC.
PHONE: 740-281-0136
www.contenderperformance.com